

Continually perfecting the simplicity and performance of premium currency counters.

Premium is defined by performance, not defined by size. The compact Model 35-3 represents the third generation in a family of outstanding price/performers, which also boasts the #1 selling table-top currency counter in the world. Along with its appealing appearance, the 35-3 offers robust functionality with automatic start, full error detection, adjustable speed, variable currency batching, and accumulation mode. At speeds up to 1500 notes per minute, basic currency counting applications can be performed with greater efficiency and optimum productivity.

MAGNER®

35-3




Proven Performance and Quality

MAGNER® Model 35-3

One word best describes the Model 35-3...**overachiever**. It is a compact premium Currency Counter designed for outstanding performance in basic currency processing applications. It offers simplicity of operation and a host of standard features such as selectable speeds up to 1500 notes per minute, automatic start, variable batching, accumulation mode and full error detection. Designed from the beginning for superior reliability and dependability, the Model 35-3 is engineered to deliver MAGNER® quality performance for the long haul.

Our Currency Counters have evolved from years of experience and are backed by unmatched support through our network of MAGNER® Authorized Distributors.



Local Representative:



9452 Telephone Rd. (#110)
Ventura, CA 93004
805-218-6106 FX 805-435-1941
www.usbanksupply.com

Model 35-3 Specifications

Counting Speed:

600,1200,1500 notes
per minute (selectable)

Display Type:

3 digit batch display
4 digit total display

Document Size Limits:

1.97" x 3.35" to 4.33" x 7.28"
50 x 85 mm to 110 x 185 mm

Hopper Capacity:

300 circulated notes

Stacker Capacity:

200 circulated notes

Batching:

Variable 1 to 999
(entry via ten-key pad)

Error Detection:

Double, chain, half-note,
and jam

Document Feed Mechanism:

Friction, intermittent roller type

Dimensions:

10.04" (H) x 11.02" (W) x 9.65" (D)
255 mm (H) x 280 mm (W) x 245 mm (D)

Net Weight:

12.1 lbs. (5.5 kg.)

Power Source:

AC115V +/- 10%, 60/50Hz
AC230V +/- 10%, 60/50Hz
(switch selectable)

Power Consumption:

40W (average)

Operating Temperature Limits:

+32° F to +104° F (0° C to +40° C)

Density Setting:

Adjustable, 5 levels

Options:

RS232C interface
External display

Other Standard Features:

Integrated carrying handle
Accumulation mode
Automatic/manual start
External thickness adjustment